



A British Brand Of High Quality Solar Modules

UKSOL PV modules are produced with high quality materials and are designed to deliver the maximum return on your investment. UKSOL modules are supported by a British 12 year product warranty and a 30 year performance warranty. The performance warranty provides for 90% of normal output for 12 years and 80% of normal output up to 30 years. Service and support is provided from our UK offices based in Coventry, UK.

Model UKSOL AS-6M30 Monocrystalline Module

Advanced Performance & Proven Advantages


- High module conversion efficiency up to 16.90% through advanced manufacturing technology.
- Low degradation and excellent performance under high temperature and low light conditions.
- Robust aluminum frame ensures the modules to withstand wind loads up to 2400Pa and snow loads up to 5400Pa.
- Positive power tolerance of 0 ~ +3 %.
- High ammonia and salt mist resistance.
- Potential induced degradation (PID) resistance.

Quality Certificates

- IEC61215, IEC61730, IEC62716, IEC61701, UL1703, CE, ETL(USA), JET(Japan), J-PEC(Japan), MCS(UK), CEC(Australia), FSEC(FL-USA), CSI Eligible(CA-USA), Israel Electric(Israel), Kemco(South Korea), InMetro(Brazil), TSE(Turkey)
- ISO9001:2008: Quality management system
- ISO14001:2004: Environmental management system
- OHSAS18001:2007: Occupational health and safety management system

Special Warranties

- 12 year limited product warranty.
- Limited power warranty: 12 years 91.2% of the nominal power output, 30 years 80.6% of the nominal power output.



30 year British warranty



Electrical Characteristics at STC

Nominal Power (Pmax)	250W	255W	260W	265W	270W	275W
Open Circuit Voltage (Voc)	37.3V	37.4V	37.5V	37.6V	37.7V	37.8V
Short Circuit Current (Isc)	8.72A	8.82A	8.91A	9.01A	9.10A	9.20A
Voltage at Nominal Power (Vmp)	30.5V	30.6V	30.7V	30.8V	30.9V	31.0V
Current at Nominal Power (Imp)	8.20A	8.34A	8.48A	8.61A	8.74A	8.88A
Module Efficiency (%)	15.37	15.67	15.98	16.29	16.60	16.90
Operating Temperature	-40° C to +85° C					
Maximum System Voltage	1000V DC					
Fire Resistance Rating	Type 1 (UL 1703)/Class C (IEC61730)					
Maximum Series Fuse Rating	15A					

STC : Irradiance 1000W/m², Cell Temperature 25°C, Air Mass 1.5

Electrical Characteristics at NOCT

Nominal Power (Pmax)	184W	188W	191W	195W	199W	202W
Open Circuit Voltage (Voc)	34.3V	34.4V	34.5V	34.6V	34.7V	34.8V
Short Circuit Current (Isc)	7.06A	7.14A	7.22A	7.30A	7.39A	7.45A
Voltage at Nominal Power (Vmp)	27.8V	27.8V	27.9V	28.0V	28.1V	28.2V
Current at Nominal Power (IN)	6.62A	6.77A	6.85A	6.97A	7.09A	7.17A

NOCT: Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1 m/s

Mechanical Characteristics

Cell Type	Monocrystalline 156x156mm (6x6 inches)
Number of Cells	60 (6x10)
Module Dimensions	1640x992x40mm (64.57x39.06x1.57 inches)
Weight	18.5kg (40.8 lbs)
Front Cover	3.2mm (0.13 inches) low-iron tempered Glass
Frame	Anodized
Junction Box	IP67, 3 diodes
Cable	4mm ² (0.006 inches ²), 900mm (35.43inches)
Connector	MC4 or MC4 Compatible


Temperature Characteristics

Nominal Operating Cell Temperature (NOCT)	45° C ± 2° C
Temperature Coefficient Of Pmax	-0.43%/°C
Temperature Coefficient Of Voc	-0.33%/°C
Temperature Coefficient Of Isc	0.056%/°C


Packaging

Standard Packaging	26 pcs / Pallet
Module Quantity per 20' Container	312 pcs
Module Quantity per 40' Container	728 pcs


ENGINEERING DRAWINGS



IV CURVES



Current-Voltage & Power-Voltage Curves At Different Irradiances



Current-Voltage Curves At Different Temperatures